

PERFECT SOLUTIONS FOR GAS ALARM SYSTEMS



Technical Datasheet



Poly Gard[®] 2

Sensor SC2

with Semiconductor Sensor Element
for Toxic Gases

DESCRIPTION

APPLICATION

FEATURES

SPECIFICATIONS

ORDER ING INFORMATION



■ All Products
■ Made
■ in Germany



 **Teléfonos**

España (+34) 609 604 054
Perú (+51) 1 6449147
Colombia (+57) 300 929 5080

 **Email**

comercial.espana@fricaval89.com
comercial.peru@fricaval89.com
comercial.colombia@fricaval89.com

 **Web**

www.fricaval89.com

DESCRIPTION

Exchangeable sensor including digital value processing and self-control for the continuous monitoring of the ambient air.

The Sensor SC2 includes a semiconductor sensor element and an amplifier as well as a μ Controller for processing of the measured values. All relevant data and measured values of the sensor element are stored fail-safe in the μ Controller and digitally transmitted via the local bus to the Sensor-Board (e.g. SB2 or MSB2). The calibration management is also integrated in the μ Controller of the Sensor.

Calibration is done either by simply replacing the Sensor or by using the comfortable, integrated calibration routine directly at the system.

APPLICATION

The PolyGard[®]2 Sensor SC2 is used for the detection of toxic gases in a variety of applications.

FEATURES

- Digital measurement value processing
- Internal functional control with integrated Hardware Watchdog
- Data/measured values in μ C of the Sensor, therefore simple exchange of Sensor uncalibrated <> calibrated
- Low zero-point drift
- Sensor with long life expectancy
- Modular technology (plug-in and replaceable)
- Easy maintenance and calibration by exchange of the Sensor or by comfortable on-site calibration
- Reverse polarity protected, overload and short-circuit proof
- IP65 version
- Conformity to:
 - EN 378
 - EN 45544-1, -3
 - EN 61010-1
 - ANSI/UL 61010 1
 - CAN/CSA-C22.2 No. 61010-1
- Duct mounting kit (accessory)



Option: SC2 in plastic housing L with cable extension (fig. w/o laser engraving)

SPECIFICATIONS

ELECTRICAL	
Power supply	5 V DC from Sensor-Board (e.g. SB2/MSB2), reverse polarity protected
Power consumption:	160 mA, max. (0.8 VA)
Serial interface local bus	1-wire / 19200 Baud
SENSOR ELEMENT	
Gas type	See Ordering Information
Sensor element	Semiconductor sensor
Pressure range	90–110 kPa
Storage temperature range	0 °C to +50 °C (32 °F to 122 °F)
Storage time ¹	Ca. 12 months
Poisoning	The sensitivity of semiconductor sensors can be affected by substances containing silicone and they may even lead to the complete poisoning. The sensors are also susceptible to poisoning by organic solvents.
PHYSICAL	
Housing in plastic	Polycarbonate
Combustion	UL 94 V2
Housing colour	RAL 7032 (light grey)
Dimensions: Housing type P	(D x H) 24 x 22 mm (0.94 x 0.87 in.)
Housing type L	(D x H) 24 x 30 mm (0.94 x 1.18 in.)
Weight	Ca. 30 g (0.07 lb)
Protection class	IP65
Mounting	Screw mounting
Connection type	3-pin connector
Cable length	Ca. 150 mm (5.91 in.) standard version w/o cable extension
REGULATIONS	
Directives (only in connection with the Sensor-Boards from MSR)	EMC Directives 2014/30/EU CE Conformity to: EN 378 EN 45544-1, -3 EN 61010-1:2010 ANSI/UL 61010-1 CAN/CSA-C22.2 No. 61010-1
Warranty	1 year on sensor (not if poisoned or overloaded), 2 years on device

¹ If stocked for a longer period, we recommend checking the zero point and recalibrating if necessary.

Gas type	Ordering No.	Measuring range	Repeatability	t ₉₀ time	Temperature range	Humidity (non-condensing)	Lifetime in air	Relative gas density	Mounting height	Calibration interval ¹
	SC2-	ppm	<± % sig.	≤ sec	°C	% RH	> months	Air = 1	(m)	Months
NH ₃	S2125-C	0–1000	20	30	-30 / +60	15–90	60	0.60	Ceiling	12
NH ₃	S2125-F	0–10,000	20	30	-30 / +60	15–90	60	0.60	Ceiling	12
C ₂ H ₄	S2189-A	20–2000	20	10	-30 / +60	15–90	60	0.97	1.5–1.8	12

¹ Manufacturer-recommended calibration interval for normal environmental conditions

No cross-sensitivity data is available for these sensors. It is well known that all semiconductor sensors are also sensitive to combustible gases, e.g. alcohols, etc.

All specifications were collected under optimal test conditions.

We confirm compliance with the minimum requirements of the applicable standard.

ORDERING INFORMATION

SC2 -	S21XX-X-	X-	XX	
			00	Without cable extension (standard) (Standard)
			XX ¹	With cable extension : 01, 02, 03, 04, 05 ...15 max. (length in m)
				Cable
		P		Sensor housing plastic (standard)
		L		Sensor housing plastic long (only with cable extension)
		S		Sensor housing stainless steel (only with cable extension)
				Sensor housing
				Gas type measuring range
	S2125 -C*			Ammonia, NH ₃ 0–1000 ppm
	S2125 -F*			Ammonia, NH ₃ 0–10,000 ppm
	S2189 -A ²			Ethylene, C ₂ H ₄ 20–2000 ppm
				Gas type/ measuring range

* Only on request

¹ Sensor housing plastic in combination with cable extension only type L

² Not in combination with stainless steel sensor housing

EXAMPLE

Ethylene Sensor, plastic housing without cable extension, measuring range 20–2000 ppm

Order number: SC2-S2189 -A-P-00

ACCESSORY

Duct mounting kit

Order number: C2-Z2